

Control Panel Type ABS CP 112 & CP 212

Compact control panel for one or two pumps conforming to ATEX.
Direct connect pumps up to 5.5 kW (10 A).
3-phase and single-phase versions.

Specification

- LED indication of power, pump run and alarm
- Switch for pump off-auto-manual control
- 2x16 character illuminated display
- Simple menu navigation with rotation knob
- Multiple choice of level control
 - Float switches
 - Analogue (4-20 mA) sensor
 - Built in pressure sensor for closed or open air systems
- Fused terminal for operation of optional air compressor CA 641
- Built in charger for optional backup battery
- Built in alarm buzzer
- Switching potential free alarm-relay contact
- Closing potential free alarm-relay contacts for individual pump fail indication
- One free run contact on each contactor
- Hard wired pump interlock input (Ex)
- Complete with 1.5 m power cable and CEE16 plug with phase shift possibility
- Two pump versions complete with 3 phase pump fuses
- 9 pin RS 232 port for PC interface (AquaProg tool)



Analogue values

- Level
- Motor current on all 3 phases
- Cos fi (power factor)
- Back pressure (optional sensor for pressurized systems)

Pump counters

- No of starts per pump
- Running hours per pump

Settings

- Start/stop level per pump
- Start/stop delay per pump
- Max no of pumps running
- Alternation
- Cyclic pump motion timer (exercise run)
- Emergency pump run on high float with run on time
- Amp rating (nominal motor current) for motor protection
- Number of pump runs and extra run on time for venting the air tube
- High back pressure
- Display language

Features for pump protection

- Thermal failure (Klixon or PTC)
- Overload failure
- Phase order
- Phase missing
- Leakage (DI)
- Dry run protection (low power factor)

Approved standards

- EMC emission standard EN 61000-6-3:2001
- EMC immunity standard EN 61000-6-2:2003
- LVD electrical safety EN 61010-1
- Safety of Machinery- Electrical Equipment of Machines EN 60204-1

Technical specifications:

Ambient operating temperature:	-20 to +50°C
Ambient storage temperature:	-30 to +80°C
Cabinet and mounting:	DIN rail, IP65 Mounting holes: see figure
Dimensions:	HxWxD: 370x250x123 mm
Weight:	<5kg, with battery
Humidity:	0-95% RH non-condensing
Power supply:	230/400 VAC, maximum 16A fused
Power consumption:	< 16VA
Contactors, max load:	ABB B7-30-10, 5.5 kW, 12A, coil 24 VAC
Fuses (only CP 212):	3x10A 3-pole type D circuit breakers
Fuse for external air pump:	500mA slow blow
Max load on alarm relays:	250VAC, 4A, 100VA resistive load
Max current from 12 VDC out:	50mA
Input voltage at Digital In and Block Pump:	5-24 VDC
Resistance at Digital In and Block Pump:	5 kohm
Analogue sensor:	4-20 mA
Analogue input resistance:	110 ohm
Temperature sensor:	PTC, limit: 3 kohm
Leakage sensor:	Limit: 50 kohm
Maximum length of I/O cables:	30 meters
Charge for lead-acid battery:	Max 80mA, 13.7 VDC

