





Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 100 - Passage libre 80 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	36	90	126	180	234	270	275	295	313	328	337	
		kW	A			0	600	1500	2100	3000	3900	4500	4583	4917	5217	5467	5617	
ZUG OC 100A 7.5-4-230	8 369	7.50	14.5	240	H m	11.2	10.9	10.2	9.7	7.9	5.5	3.4	3.2	-	-	-	-	
ZUG OC 100A 7.5-4-235	8 369	7.50	14.5	240		13.5	13.1	12.3	11.6	-	-	-	-	-	-	-	-	-
ZUG OC 100A 9-4-235	8 857	9.00	18.3	240		13.5	13.1	12.3	11.6	9.8	7.5	5.4	5	3.8	-	-	-	-
ZUG OC 100A 11-4-245	11 025	11.00	21.2	312.2		17.5	16.8	16	15	12.8	10.3	8.3	8	6.5	4.8	-	-	-
ZUG OC 100A 15-4-260	11 596	15.00	28.5	325.9		24.7	22.5	20.5	19.4	16.9	14	12	11.6	10.3	8.9	7	-	-
ZUG OC 100A 15-4-270	11 596	15.00	28.5	325.9		26.5	25.4	22.6	21	18.8	16	13.9	-	-	-	-	-	-
ZUG OC 100A 18.5-4-270	13 863	18.50	35.2	410.5		26.5	25.4	22.6	21	18.8	16	13.9	13.5	12.2	11	9.6	8.8	-

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	60	120	175	205	225	240	250	275	280	295	335	398	415	435	455	490	520	530	550	
		kW	A			0	1000	2000	2917	3467	3750	4000	4167	4583	4667	4917	5583	6633	6917	7250	7583	8167	8667	8833	9167	
ZUG OC 100C 22-4-290	16 962	22.00	40.6	537	H m	28	26.5	25	22.5	21	20	19	17.5	18	-	-	-	-	-	-	-	-	-	-	-	
ZUG OC 100C 30-4-290	SD	30.00	55.7	575		28	26.5	25	22.5	21	20	19	17.5	18	17.5	16.5	14.5	9.5	-	-	-	-	-	-	-	-
ZUG OC 100C 30-4-310	SD	30.00	55.7	575		36	33	29.5	27.5	26	25	24.5	24	22.5	22	21	19	15	13	-	-	-	-	-	-	-
ZUG OC 100C 30-4-330	SD	30.00	55.7	575		44.5	39.5	35.5	33.5	32	31	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 37-4-330	SD	37.00	68.5	652		44.5	39.5	35.5	33.5	32	31	30.5	30	28.5	28	27.5	25.5	22	20.5	18	-	-	-	-	-	-
ZUG OC 100C 37-4-350	SD	37.00	68.5	652		49.5	45.5	41.5	39	38	37	36.5	36	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 45-4-350	SD	45.00	80	679		49.5	45.5	41.5	39	38	37	36.5	36	34.5	34	33.5	31.5	27.5	26.5	25	23	-	-	-	-	-
ZUG OC 100C 37-4-370	SD	37.00	68.5	652		56	52	48	45.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 45-4-370	SD	45.00	80	679		56	52	48	45.5	44.5	43.5	42.5	42	40.5	40	39.5	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 55-4-370	SD	55.00	101.7	971		56	52	48	45.5	44.5	43.5	42.5	42	40.5	40	39.5	37	33.5	32.5	31.5	30	27	-	-	-	-
ZUG OC 100C 45-4-390	SD	45.00	80	679		63	59	54.5	52	51	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 55-4-390	SD	55.00	101.7	971		63	59	54.5	52	51	50	49.5	49	47.5	47	46.5	44	-	-	-	-	-	-	-	-	-
ZUG OC 100C 75-4-390	SD	75.00	137.3	1045		63	59	54.5	52	51	50	49.5	49	47.5	47	46.5	44	40	39	38	36.5	34	31	-	-	-
ZUG OC 100C 55-4-400	SD	55.00	101.7	971		67.5	62.5	58.5	56	55	54	53.5	53	52	51.5	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 75-4-400	SD	75.00	137.3	1045		67.5	62.5	58.5	56	55	54	53.5	53	52	51.5	51	48	44	43	42	41	38.5	36	35	-	-
ZUG OC 100C 55-4-412	SD	55.00	101.7	971		71	67	63	60.5	59.5	59	58.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100C 75-4-412	SD	75.00	137.3	1045		71	67	63	60.5	59.5	59	58.5	58	57	56.5	55.5	53	48.5	47.5	46.5	45	43.5	41	40	37	-

Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 100 - Passage libre 45 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	43	68	79	88	101	115	124	137	155	187	202	205	214	227	234	237	243	256	261	265	270	
		kW	A			0	717	1133	1317	1467	1577	1688	2067	2283	2583	3167	3367	3417	3567	3783	3900	3950	4050	4267	4310	4487	4500	
ZUG OC 100F 3-4-170	6 402	3.00		191	H m	10	8.5	7.6	7.1	6.9	6.4	5.7	5.1	4.5	3.5	1.8	-	-	-	-	-	-	-	-	-	-	-	
ZUG OC 100F 3-4-180	6 402	3.00		191		11.6	10.1	9	8.5	8.2	7.7	7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 4-4-180	7 026	4.00		209		11.6	10.1	9	8.5	8.2	7.7	7	6.5	5.7	4.7	2.8	1.9	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 3-4-190	6 402	3.00		191		13.2	11.7	10.3	9.8	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 4-4-190	7 026	4.00		209		13.2	11.7	10.3	9.8	9.5	8.9	8.3	7.9	7.3	5.2	4	3	2.7	2	-	-	-	-	-	-	-	-	-
ZUG OC 100F 4-4-200	7 026	4.00		209		14.9	13.2	11.9	11.3	10.9	10.3	9.8	9.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 5.5-4-200	7 273	5.50		212		14.9	13.2	11.9	11.3	10.9	10.3	9.8	9.3	8.8	7.5	5.2	4.2	3.9	3.2	2.5	-	-	-	-	-	-	-	-
ZUG OC 100F 4-4-210	7 026	4.00		209		16.5	14.8	13.4	12.7	12.2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 5.5-4-210	7 273	5.50		212		16.5	14.8	13.4	12.7	12.2	11.6	10.8	10.4	9.8	8.9	6.5	5.2	5	4.2	3	2.5	-	-	-	-	-	-	-
ZUG OC 100F 4-4-220	7 026	4.00		209		18	16.3	14.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 5.5-4-220	7 273	5.50		212		18	16.3	14.9	14.1	13.7	13	12.2	11.7	11	9.9	7.7	6.7	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 7.5-4-220	9 319	7.50		261.3		18	16.3	14.9	14.1	13.7	13	12.2	11.7	11	9.9	7.7	6.7	6.3	5.6	4.5	3.6	3.5	2.9	-	-	-	-	-
ZUG OC 100F 5.5-4-230	7 273	5.50		212		20	18.3	16.8	16.1	15.6	14.9	14	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 7.5-4-230	9 319	7.50		261.3		20	18.3	16.8	16.1	15.6	14.9	14	13.5	12.9	11.6	9.6	8.5	8.2	7.5	6.5	5.6	5.5	4.5	3	-	-	-	-
ZUG OC 100F 5.5-4-240	7 273	5.50		212		22	20.1	18.5	17.8	17.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 7.5-4-240	9 319	7.50		261.3		22	20.1	18.5	17.8	17.3	16.5	15.6	15	14.2	13.2	11.1	10.1	9.8	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 9-4-240	9 785	9.00		282.3		22	20.1	18.5	17.8	17.3	16.5	15.6	15	14.2	13.2	11.1	10.1	9.8	9.1	8.1	7.5	7.4	6.5	4.9	4.4	-	-	-
ZUG OC 100F 7.5-4-250	9 319	7.50		261.3		24	22.1	20.6	19.9	19.4	18.7	17.8	17.2	16.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 9-4-250	9 785	9.00		282.3		24	22.1	20.6	19.9	19.4	18.7	17.8	17.2	16.5	15.2	13	11.9	11.5	11	10.1	9.4	9.3	-	-	-	-	-	-
ZUG OC 100F 11-4-250	11 768	11.00		333.5		24	22.1	20.6	19.9	19.4	18.7	17.8	17.2	16.5	15.2	13	11.9	11.5	11	10.1	9.4	9.3	8.7	7.4	7	6.1	-	-
ZUG OC 100F 7.5-4-260	9 319	7.50		261.3		25.8	23.9	22.5	21.8	21.2	20.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 9-4-260	9 785	9.00		282.3		25.8	23.9	22.5	21.8	21.2	20.5	19.6	19	18.2	17	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 100F 11-4-260	11 768	11.00		333.5		25.8	23.9	22.5	21.8	21.2	20.5	19.6	19	18.2	17	14.7	13.5	13.1	12.7	11.8	11.1	11	10.3	9.4	9.1	8.2	7.5	-

SD : SUR DEMANDE Pied d'assise (prix sur demande).

# ZUG OC POMPES DE RELEVAGE À ROUE MULTI-CANAUX OUVERTE - À HAUT RENDEMENT ÉNERGÉTIQUE

Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 100 - Passage libre 65 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	29	58	92	115	144	171	184	200	209	216	223	
		kW	A			0	483	967	1533	1917	2100	2850	3067	3333	3483	3600	3717	
ZUG OC 100J 3-4-175	6 204	3.00	6.6	173	H m	7.8	6.8	5.7	4.9	4	2.7	1.7	-	-	-	-	-	
ZUG OC 100J 3-4-185	6 204	3.00	6.6	173		9.2	8.2	7	6.2	5.2	3.7	2.4	1.8	-	-	-	-	-
ZUG OC 100J 3-4-195	6 204	3.00	6.6	173		10.9	9.7	8.6	7.6	6.7	5.2	3.7	3	1.9	-	-	-	-
ZUG OC 100J 3-4-198	6 204	3.00	6.6	173		12.8	11.3	9.7	8.5	-	-	-	-	-	-	-	-	-
ZUG OC 100J 4-4-198	6 498	4.00	8.5	191		12.8	11.3	9.7	8.5	7.5	6.1	4.4	3.6	2.5	2	-	-	-
ZUG OC 100J 4-4-205	6 498	4.00	8.5	191		14.8	12.5	10.9	9.6	8.6	7.2	5.6	4.8	3.6	2.9	2.3	-	-
ZUG OC 100J 4-4-210	6 498	4.00	8.5	191		16.1	13.3	11.8	10.4	9.4	-	-	-	-	-	-	-	-
ZUG OC 100J 5.5-4-210	6 745	5.50	11.7	194		16.1	13.3	11.8	10.4	9.4	8	6.5	5.7	4.4	3.6	3	2.3	-

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	36	72	144	216	288	360	414	436	464	482	497	
		kW	A			0	600	1200	2400	3600	4800	6000	6900	7267	7733	8033	8283	
ZUG OC 150A 7.5-4-230	8 369	7.50	14.5	252.1	H m	10.9	10.6	10.2	8.9	7.1	5.2	3	1.3	-	-	-	-	
ZUG OC 150A 9-4-235	8 857	9.00	18.3	273.1		13.1	12.6	12.1	10.9	8.6	6.5	4	2	1	-	-	-	-
ZUG OC 150A 11-4-245	11 025	11.00	21.2	324.3		17.1	14.2	15.6	14	11.5	8.7	6	3.8	2.9	1.5	-	-	-
ZUG OC 150A 15-4-260	11 623	15.00	28.5	338		24.1	21.9	20.4	15.8	14.8	11.7	8.2	5.6	4.5	2.8	1.8	-	-
ZUG OC 150A 15-4-270	11 623	15.00	28.5	338		26.1	23.8	22.3	19.5	16.3	13	9.5	6.7	5.5	3.8	2.9	1.8	-

Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 150 - Passage libre 80 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	36	108	180	252	306	333	351	387	396	414		
		kW	A			0	600	1800	3000	4200	5100	5550	5850	6450	6600	6900		
ZUG OC 150D 3-4-190	5 597	3.00	6.6	177.4	H m	5.6	5.2	3.9	2.7	1.7	0.6	-	-	-	-	-	-	
ZUG OC 150D 4-4-200	6 435	4.00	8.5	211.4		6.6	6.1	4.8	3.4	2.3	1.3	0.7	-	-	-	-	-	-
ZUG OC 150D 4-4-210	6 435	4.00	8.5	211.4		7.9	7.6	6.1	4.4	3.2	2.1	1.5	1	-	-	-	-	-
ZUG OC 150D 5.5-4-220	6 689	5.50	11.7	215.4		10.2	9.6	8.1	6.2	4.5	3.2	2.5	2.1	1.2	-	-	-	-
ZUG OC 150D 7.5-4-221	8 534	7.50	14.5	247.7		11.7	11.1	9.6	7.5	5.4	4	3.3	2.6	1.5	1.3	-	-	-
ZUG OC 150D 7.5-4-222	8 534	7.50	14.5	247.7		13.4	12.9	10.8	8.6	6.4	4.9	4.2	3.5	2.3	1.9	1.3	-	-

Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 200 - Passage libre 80 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	72	144	216	288	360	432	504	580	621	713	724	745	770	817	
		kW	A			0	1200	2400	3400	4800	6000	7200	8400	9667	10350	11883	12067	12417	12833	13617	
ZUG OC 200B 11-4-240	11 639	11.00	21.2	352	H m	12.4	11.6	10.3	8.8	7.6	6.5	5.3	3.9	2	-	-	-	-	-	-	
ZUG OC 200B 11-4-255	11 639	11.00	21.2	352		14.8	13.7	12.1	10.7	9.5	8	6.6	5	3.2	2	-	-	-	-	-	-
ZUG OC 200B 15-4-269	12 236	15.00	28.5	365		19	16.7	16	14.2	12.8	11	9.2	7.2	5.1	3.8	2	-	-	-	-	-
ZUG OC 200B 18.5-4-275	14 711	18.50	35.2	451		26.7	23.2	20.7	18.8	16.6	14.4	12	9.6	7	5.2	3.1	2.1	-	-	-	-
ZUG OC 200B 22-4-290	16 167	22.00	40.6	468		30.5	27	24.1	21.8	19.7	17.5	14.9	12.1	9.2	7.5	5.3	4.1	2	-	-	-
ZUG OC 200B 30-4-305	SD	30.00	55.7	506		33.5	30	27.2	24.9	22.3	20	17.2	14.2	11.5	9.7	7	6	3.8	2.1	-	-
ZUG OC 200B 30-4-315	SD	30.00	55.7	506		36.1	32.5	29.8	25.6	25	22.6	20	17.1	14	12.1	9.8	8.5	6.2	4.8	2.1	-

Moteur 400 volts - 1450 tours/minute.  
 Refoulement horizontal DN 200 - Passage libre 100 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	150	300	450	550	685	756	790	892	1000	1150	1250	1340	1370	1400	1410	1420	
		kW	A			0	2500	5000	7500	9167	11417	12600	13167	14867	16667	19167	20833	22333	22833	23833	23500	23666	
ZUG OC 200C 90-4-395	SD	90.00	167	1500	H m	43	41	38	34.5	32	29	27.5	26.5	24	22	18	15	11	-	-	-	-	
ZUG OC 200C 90-4-405	SD	90.00	167	1500		47.5	45	41.5	38	36	32.5	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 200C 110-4-405	SD	110.00	206	1574		47.5	45	41.5	38	36	32.5	30.5	29	27	25	21	17.5	14	13	-	-	-	-
ZUG OC 200C 110-4-420	SD	110.00	206	1574		51.5	48.5	45.5	42	39	36	34	33.5	31	28	24	21	17.5	16	15	-	-	-
ZUG OC 200C 110-4-430	SD	110.00	206	1574		57	53	49.5	46	43	39.5	38	37	-	-	-	-	-	-	-	-	-	-
ZUG OC 200C 132-4-430	SD	132.00	238	1728		57	53	49.5	46	43	39.5	38	37	34	33	27	24	20.5	19	18	12	-	-
ZUG OC 200C 110-4-440	SD	110.00	206	1574		61	57	53	49	-	-	-	-	-	-	-	-	-	-	-	-	-	-
ZUG OC 200C 132-4-440	SD	132.00	238	1728		61	57	53	49	46	43	41	40	37	34	30	26	23	22	20	19.5	19	-
ZUG OC 200C 132-4-455	SD	132.00	238	1728		70	63	58	53	50	46.5	44.5	43.5	41	-	-	-	-	-	-	-	-	-
ZUG OC 200C 160-4-455	SD	160.00	285	1884		70	63	58	53	50	46.5	44.5	43.5	41	37.5	33	30	26.5	25	24	23	-	-
ZUG OC 200C 160-4-465	SD	160.00	285	1884		75.5	69	63	58.5	55.5	51.5	50	48.5	45.5	42.5	38	34	30.5	29	27.5	27	26.5	-
ZUG OC 200C 185-4-480	SD	185.00	331	1884		81	75	70	65	61.5	57	54.5	53.5	50	47	42.5	39	36	34.5	33	32.5	31.5	-
ZUG OC 200C 185-4-490	SD	185.00	331	1884		88	82	77.5	73.5	70.5	66	63	-	-	-	-	-	-	-	-	-	-	-

## ZUG OC POMPES DE RELEVAGE À ROUE MULTI-CANAUX OUVERTE - À HAUT RENDEMENT ÉNERGÉTIQUE



Moteur 400 volts - 1450 tours/minute.  
Refoulement horizontal DN 200 - Passage libre 80 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	160	280	440	560	684	709	800	886	910	1040	1130	1150
		kW	A			0	2667	4667	7333	9333	11400	11817	13333	14767	15167	17333	18833	19167
ZUG OC 200G 90-4-420	SD	90.00	167	1521	H m	62	54	50.5	46	42.5	38.5	38	-	-	-	-	-	-
ZUG OC 200G 110-4-420	SD	110.00	206	1595		62	54	50.5	46	42.5	38.5	38	35	32.5	31.5	26	23	-
ZUG OC 200G 110-4-440	SD	110.00	206	1595		68.5	60	56	51.5	47.5	43.5	43	40	37	36.5	-	-	-
ZUG OC 200G 132-4-440	SD	132.00	238	1749		68.5	60	56	51.5	47.5	43.5	43	40	37	36.5	31.5	27.5	-
ZUG OC 200G 110-4-460	SD	110.00	206	1595		75.5	67	62	57.5	53	-	-	-	-	-	-	-	-
ZUG OC 200G 132-4-460	SD	132.00	238	1749		75.5	67	62	57.5	53	49	48	45	42	41	37	33	32
ZUG OC 200G 132-4-480	SD	132.00	238	1749		82.5	72.5	68.5	63.5	59	55	-	-	-	-	-	-	-
ZUG OC 200G 160-4-480	SD	160.00	285	1905		82.5	72.5	68.5	63.5	59	55	54	51	48	47	42	38	37
ZUG OC 200G 160-4-500	SD	160.00	285	1905		89.5	78.5	74.5	69.5	66	61	60.5	57	53.5	-	-	-	-


Moteur 400 volts - 1450 tours/minute.  
Refoulement horizontal DN 250 - Passage libre 110 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	200	400	600	800	1035	1200	1400	1610	1630	1725	1892	2010	2040
		kW	A			0	3333	6666	10000	13333	17250	20000	23333	26833	27167	28750	31533	33500	34000
ZUG OC 250C 45-4-334	SD	45.00	80	673	H m	38.5	32.5	27	21	14	3.5	-	-	-	-	-	-	-	-
ZUG OC 250B 90-4-345	SD	90.00	167	1437		37.5	34.5	32	28.5	24	19.5	17	14	9.5	-	-	-	-	-
ZUG OC 250B 90-4-360	SD	90.00	167	1437		41.5	37.5	35	31.5	27.5	23	19	16	11.5	10.5	-	-	-	-
ZUG OC 250B 110-4-385	SD	110.00	206	1511		50	43.5	41	38	34	28.5	24.5	20.5	16	15	12.5	-	-	-
ZUG OC 250B 132-4-410	SD	132.00	238	1665		58.5	51.5	47	44	40.5	35	30.5	26	20.5	19	17	12	-	-
ZUG OC 250B 160-4-440	SD	160.00	285	1821		68.5	61	56	52.5	48	42.5	38.5	33	27	26	23	19	14	-
ZUG OC 250B 185-4-460	SD	185.00	331	1821		73	66	63	58.5	54	48	43	37.5	31.5	30	27	22.5	18	15.5

Moteur 400 volts - 1450 tours/minute.  
Refoulement horizontal DN 250 - Passage libre 80 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	80	180	280	400	520	672	712	740	765	790	830	875
		kW	A			0	1333	3000	4667	6667	8667	11200	11867	12333	12750	13167	13333	14583
ZUG OC 250H 11-4-240	12 405	11.00	21.2	383	H m	11.8	10.9	9.2	7.9	6.3	4.2	1.2	-	-	-	-	-	-
ZUG OC 250H 15-4-255	13 012	15.00	28.5	396		14.2	13.1	11.5	9.7	7.9	5.7	2.3	1.5	-	-	-	-	-
ZUG OC 250H 15-4-269	13 012	15.00	28.5	396		18.3	16.6	14.8	12.7	10.5	7.7	3.8	2.9	2.1	-	-	-	-
ZUG OC 250H 18.5-4-275	15 084	18.50	35.2	481		25.5	21.6	19	16.5	13.3	10	5.2	3.8	2.9	1.7	-	-	-
ZUG OC 250H 22-4-290	16 556	22.00	40.6	498		29.1	25	22	17.5	16.2	12.2	6.8	5.3	4.1	3	2	-	-
ZUG OC 250H 30-4-305	SD	30.00	55.7	536		32.6	28.1	24.8	22.2	19	15	9.4	7.5	6.5	5.4	4.3	2	-
ZUG OC 250H 30-4-315	SD	30.00	55.7	536		35.1	30.2	27	24.3	21	17	11.3	9.7	8.7	7.6	6.6	4.5	2.1

## ZUG HP POMPES DE RELEVAGE À ROUE MULTI-CANAUX OUVERTE - À HAUT RENDEMENT ÉNERGÉTIQUE



Moteur 400 volts - 2900 tours/minute.  
Refoulement horizontal DN 32 G2" - Passage libre 10 mm.

Référence	€ HT	MOTEUR		Kg	m³/h l/min	0	6	10	14	18	22	23.4	26.4	30	33	39
		kW	A			0	100	167	233	300	367	390	440	500	550	650
ZUG HP 050B 5.5-2-190	SD	5.50	10.2	121	H m	46.1	45.5	45	44.6	43.9	43	42.5	-	-	-	-
ZUG HP 050B 7.5-2-190	SD	7.50	14.12	134		46.1	45.5	45	44.6	43.9	43	42.5	41.5	39.9	38.4	34
ZUG HP 050A 7.5-2-185	4 663	7.50	14.12	129		51.6	48.5	46	43.6	41.2	38.5	37.4	35.1	31.9	27.8	-
ZUG HP 050A 9.2-2-190	5 138	9.20	16.5	133		54	51.9	47.5	45.1	44.5	41.6	40.5	38.1	35	30.5	-
ZUG HP 050A 7.5-2-196	4 663	7.50	14.12	129		58.3	56.2	53.5	51.4	48.6	45.5	44.5	42.1	-	-	-
ZUG HP 050A 9.2-2-196	5 138	9.20	16.5	133		58.3	56.2	53.5	51.4	48.6	45.5	44.5	42.1	38.8	34.5	-